

Eggshell

A superior, mid-sheen, hard wearing, solvent-based finish ideal for interior wood and metal surfaces. Offers excellent sag resistance and easy application.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Wood and metal.

Colour availability

Brilliant White, Black and Magnolia (5ltr, 2.5ltr & 750ml). Thousands of tinted colours also available (5ltr, 2.5ltr & 1ltr)

Finish

Mid Sheen

Volume solid

56%

Coverage

1 litre will cover approximately 20 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 4-6 hours.
Recoat after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300 g/l (2010). This product contains max 300 g/l VOC.

Film thickness

Wet: 50µm
Dry: 28µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the

appropriate Leyland Primer. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Apply evenly by brush or roller and avoid overspreading. Apply one or more coats as required and allow 16-24 hours drying between coats under normal conditions. Do not apply over polystyrene surfaces.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly after use.

Warning

- Flammable liquid and vapour.
- Contains 2-butanone oxime.
- May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.



Whilst we use the latest technology in our paints, the nature of solvent based trim products means that they have the potential to yellow over time, when exposed to certain conditions. For a finish that stays whiter for longer, please use Leyland Trade Fast Drying Satin.